



AnyQuest Enhanced Cyble

Radio Module for Mobile AMR

Built on Itron proven expertise to design and manufacture high performance radio modules, AnyQuest Enhanced is the significant next evolution step going far beyond the simple reading of the actual meter index for billing purpose.

Mobile meter data collection systems have been widely adopted by utilities and service companies. This mature technology significantly accelerates meter reading speed and avoids risk of visual reading mistakes. It also largely improves meter readers safety and customer satisfaction - avoiding intrusion in private facilities.

AnyQuest Enhanced offers the benefits of unprecedented functionalities within a mobile data collection system. Whether your challenge is to reduce non-revenue water, manage water conservation programs, or increase operation efficiency, the versatility of AnyQuest Enhanced functionalities provides you all the necessary tools.

ENHANCED FUNCTIONALITIES

AnyQuest delivers a comprehensive list of functionalities to get the most out of the mobile data collection process.

*functions also available with EverBlu Cyble Enhanced (Fixed network ready)

015	Volume index	Volume index at time of reading
1111	Preset billing date	Volume index recorded at 4 preset dates (programmable)
	Data-logging	History of up to 181 consumption intervals (hourly,daily,weekly,monthly)
10	2 Time-Of-Use Indexes	Registers consumption within a defined intervals of the year
	Volume above threshold	Total consumption above a high flow-rate threshold
	Volume below threshold	Total consumption below a low flow-rate threshold
	Meter sizing indicators	2×13 monthly indicators if the meter is oversized or undersized
₫!	Leakage information	13 month history of number of leakage days
	Backflow volume and alarm	Total backflow volume and 13 monthly alarms
	Meter stopped detection	Alarm if no consumption over a configurable period has been recorded
	Reversed meter detection	Alarm if > 1000 consecutive target turns in reverse flow have been recorded
	Module tamper detection	Alarm if the radio module module has been tampered
	Alarm log	Log of start and end dates for last recorded alarms
	Peak flow-rates	5 highest peak flow-rate values with date of occurrence
11	Peak flow alams	13 monthly alarms if the peak flow threshold has been exceeded



AnyQuest Software

Functional Specifications				
Dimensions	92 x 57 x 50 mm			
Power source	Lithium battery			
Battery lifetime (min)*	15 years			
Case protection	IP68			
Relative humidity	0 to 100% - submersible			
Operating temperature **	-10°C / +55°C***			
Accidental temperature	-20°C / +70°C			
Conformity	← certified, in accordance with the European R&TTE directive (1999/5/EC)			

* Under normal applications within the specified reference operating conditions.

^{***} Operation: $+5^{\circ}$ C to $+35^{\circ}$ C / Storage: $+5^{\circ}$ C to $+35^{\circ}$ C / Transport: Min. -20° C (<24 hours continuous), Max. $+70^{\circ}$ C (<24 hours continuous)/Min. operational temperature: -10° C (<15 days/years)/Max. operational temperature: $+55^{\circ}$ C (<15 days/years).

Radio Frequency Features			
Protocol	RADIAN		
Modulation	Frequency Shift Keying		
Frequency carrier	433.82 MHz		
Radiated power	≤ 10 mW		
Transmission	Symmetrical 2-way communication		
Line of sight reading distance (LOS)	> 1500m		



Our company is the world's leading provider of smart metering, data collection and utility software systems, with over 8,000 utilities worldwide relying on our technology to optimize the delivery and use of energy and water.

To realize your smarter energy and water future, start here: www.itron.com

For more information, contact your local sales representative or agency:

ITRON WATER METERING

9, rue Ampère 71031 Mâcon cedex France

Phone: +33 3 85 29 39 00 **Fax:** +33 3 85 29 38 58

While Itron strives to make the content of its marketing materials as timely and accurate as possible, Itron makes no claims, promises, or guarantees about the accuracy, completeness, or adequacy of, and expressly disclaims liability for errors and omissions in, such materials. No warranty of any kind, implied, expressed, or statutory, including but not limited to the warranties of non-infringement of third party rights, title, merchantability, and fitness for a particular purpose, is given with respect to the content of these marketing materials. © Copyright 2011, Itron. All rights reserved. SYS-0029.2-EN-09.11

^{**} High Temperature (HT) version also available on request.